

MARINE

High performance marine grease

Innovating for tomorrow



TECHNICAL DATA SHEET

Quality Standards:
ISO 9001:2008
ISO 14001: 2004

Issue Date: March 2016

HIGH LOAD 1 & 2

High quality lithium soap thickened grease containing extreme pressure additives, high load solids and corrosion inhibitors offering good salt water protection. Available in NLGI grades 1 and 2.



Typical Characteristics

Colour	Grey/Black
Texture	Smooth
Thickener Type	Lithium
Drop Point	175°C
NLGI Grade	No. 1 (Also available in No.2)
Emcor (Water)	0:0
Timken OK Load	60lbs
Weld Load (IP239)	450kg
Water Washout	Less than 5%
Pumpability	-20°C

Applications

- Anti-friction and plain bearings of moderate speed and especially large diameter slow speed bearings. Also for use in:
 - Slew rings
 - Pins
 - Bushes
 - Trunnions
 - Levers
 - Oscillating Equipment
 - Levers
 - Pulleys
 - Couplings and
 - Wheel Bearings
- May be applied through automatic and semi-automatic heavy duty grease systems
- Can also be used in rail applications on heavily loaded curves where additional protection from boundary lubrication is required

Features and Benefits

- Extends equipment life
- Economic in use—low contamination
- Extends re-lubrication intervals
- Will help reduce noise

Pack Size	RS Clare Product Reference Code
9x2kg	D0847/00/19CTN
24x400g	D0847/00/24CTN
12.5kg	D0847/00/12.5kg
50kg	D0847/00/50kg
180kg	D0847/00/180kg

The information contained herein may change. While every care is taken to ensure the accuracy of the material contained in this bulletin, no liability can be assumed for the information given. For specific, current information please contact Clare field sales staff.