

# MARINE

High performance marine grease

*Innovating for tomorrow*



## TECHNICAL DATA SHEET

Quality Standards:  
ISO 9001:2008  
ISO 14001: 2004

Issue Date: March 2016

## WATERGUARD (SW2-LF)

A mixed lithium and calcium soap thickened grease providing enhanced thermal stability and excellent water resistance. A lubricating grease specifically developed for the lubrication of wire ropes, bearings and other mechanical components operating in salt water conditions.



### Typical Characteristics

Colour	Beige
Texture	Adhesive
Thickener Type	Lithium, Calcium
Drop Point	>180°C
Worked Penetration	265-295
Emcor (3% NaCl)	0:0
Flash Point	220°C
Pour Point	-20°C

### Applications

A variety of applications where water wash-off and salt water corrosion are an issue e.g. wire ropes in submerged conditions, rolling elements, plain bearings, open gears, threaded spindles and sliding mechanisms.

### Features and Benefits

- Optimum corrosion protection
- Highly adhesive and cohesive
- High operating temperatures
- Excellent sealing properties against cold or warm water
- Good extreme pressure properties

Pack Size	RS Clare Product Reference Code
9x2kg (19CTN)	D0787/00/19CTN
24x400g (24CTN)	D0787/00/24CTN
12.5kg	D0787/00/12.5kg
50kg	D0787/00/50kg
180kg	D0787/00/180kg

The information contained herein may change. While every care is taken to ensure the accuracy of the material contained in this bulletin, no liability can be assumed for the information given. For specific, current information please contact Clare field sales staff.