



Quality Standards: ISO 9001:2015 ISO 14001: 2015 Issue Date—Feb 2020 Revision—02

CLARETECH ECOCURVE HEAVY HAUL

Environmentally friendly All Season curved rail protection on Heavy Haul and Class 1 railways.
NLGI 1.5

Applications

Suitable for use in all makes of trackside lubricators wherever there is a requirement for a high performance and environmentally friendly lubricant.

Can be used to lubricate and protect high load curved rails over long distances, and for the lubrication of check rails and switchblades.

Features and Benefits

- Biodegradable and suitable for use near rivers and watercourses
- Non-toxic and non-bioaccumulative.
- Extreme load performance to minimise rail wear
- Highly adhesive, while giving excellent carry down
- Oxidation stable does not dry or stiffen to block lubricator GDU ports
- Stable across a wide temperature range one grease for all seasons
- Suitable for high traffic networks and heavy axel loads
- Lasting protection to reduce corrosion defects
- RS Clare's EcoCurve range incorporates breakthrough nanotechnology at the molecular level to increase stability, consistency and performance whilst minimising the need for harmful chemical additives.

Typical Character	istics	
Appearance	Visual	Smooth
Colour	Visual	Black/Grey
Thickener Type		Complex
Temperature Range		-40°C to 120°C
Worked Penetration	IP 50	290 - 310
Drop Point	IP 396	170°C
Oil Separation (40°C, 168hrs)	IP 121	<5%
4-Ball Wear Scar	IP 239	0.5mm
4-Ball Weld Load	IP 239	620kg
Emcor Corrosion (distilled water)	IP 220	0,0
Copper Corrosion (100°C, 24hrs)	IP 122	1a
Water Wash Out	ASTM D1264	4%
Biodegradability	OECD 301B	PASS - Readily Biodegradable
Base Oil Characteristics		
Туре		Synthetic Ester
Kinematic Viscosity (40°C)	ASTM D445	45cSt
Flash Point	IP 34	>220°C
Pour Point	IP 15	-30°C
USA Environmentally Acceptable Lubricant		Yes



