

RAIL

High performance P-way lubrication
Innovating for tomorrow



TECHNICAL DATA SHEET

Product code: D0269
Quality Standards:
ISO 9001:2015
ISO 14001: 2015
Issue Date—March 2018
Revision—01

All Seasons P Way Lubricant

Long life fishplate lubricant.
NLGI 00

Applications

Experienced Rail Engineers know that while some products claim to penetrate clamped Fishplate joint, the only way to be sure of getting a long lasting high strength grease between Fishing surfaces is to loosen and to spray with All Seasons P Way.

This long established product typically provides two years of lubrication between re-applications, reducing the risk of Rail bucking due to temperature variations.

Features and Benefits

- Long life lubricant for extended service intervals
- Extreme Pressure lubricant to allow controlled joint movement
- Excellent corrosion protection to the hidden Fishing surfaces
- No run-off after application, reducing pollution risk
- Brush or spray application for fast servicing of Fishplates

Typical Characteristics

Appearance	Visual	Semi-fluid
Colour	Visual	Black
Thickener Type		Calcium
Temperature Range		-30°C to 50°C
4 Ball Wear Scar	IP 239	0.6mm
Copper Corrosion (100°C, 24hrs)	IP 122	1b

Base Oil Characteristics

Type		Mineral/Solvent
Flash Point (Closed Cup)	IP 34	70°C

Please Note

Network Rail and London Underground approved Backpack Spray units can be supplied. Details are on our website.



The information contained herein may change. Whilst every care is taken to ensure the accuracy of the material contained in this bulletin, no liability can be assumed for the information given. For specific, current information please contact Clare field sales staff.