

RAIL

High performance switchplate
lubricant
Innovating for tomorrow



TECHNICAL DATA SHEET

Product code: D0112
Quality Standards:
ISO 9001:2015
ISO 14001: 2015
Issue Date—July 2018
Revision—01

ClareTech BioGlide

Long life lubrication for slide chairs or switchplates of railway switches.
NLGI 000

Applications

For use on switchplates where there is a requirement for a high performance and environmentally friendly product.

Can be quickly and easily applied from a High Pressure Backpack Spray Unit or by brush with re-lubrication intervals from 3 to 6 weeks depending on frequency of switch movements.

Features and Benefits

- Biodegradable
- Clean to use
- Contains a durable film of lubrication which reduces wear to prolong switchplate life
- Highly adhesive and water resistant, giving long-

Typical Characteristics

Appearance	Visual	Fluid
Colour*	Visual	Yellow
Thickener Type		Complex
Temperature Range		-40°C to 60°C
Unworked Penetration	IP 50	445-475
Oil Separation (40°C, 168hrs)	IP 121 (MOD)	8%
4 Ball Wear Scar	IP 239	0.5mm
4 Ball Weld Load	IP 239	250kg
Copper Corrosion (100°C, 24hrs)	IP 122	1a

Base Oil Characteristics

Type		Ester
Kinematic Viscosity (40°C)		45cSt
Flash Point	IP 34	220°C
Pour Point	IP 15	-30°C
USA Environmentally Acceptable Lubricant		Yes

* Note: The product will exhibit a slight change of colour after exposure to air. This is a normal and expected feature of the unique chemistry employed in this grease. This feature has been assessed as having no effect on the product performance.



The information contained herein may change. Whilst every care is taken to ensure the accuracy of the material contained in this bulletin, no liability can be assumed for the information given. For specific, current information please contact Clare field sales staff.

 **RS Clare & Co Ltd**
Innovation since 1748