

RAIL

High performance, curved rail
lubricant

Innovating for tomorrow



TECHNICAL DATA SHEET

Product code: D0060
Quality Standards:
ISO 9001:2015
ISO 14001: 2015
Issue Date - February 2020
Revision - 01

ClareTech Rail King HL

High performance multi-season curved rail grease for trackside lubricators.
NLGI 1.5

Applications

Rail King HL is for use in trackside lubricators wherever there is a need for a high performance and consistent delivery over a wide temperature range. Suitable for high traffic networks and heavy axle loads.

Features and Benefits

- Contains molybdenum disulfide (MoS₂) for improved wear reduction and extreme pressure resistance.
- Clean to use - reduced fling-off in surrounding areas.
- Enhanced anti-wear performance and high load protection to minimise rail wear.
- Oxidation stable - does not dry or stiffen to block lubricator ports.
- Water resistant, giving lasting protection to reduce corrosion defects.
- Highly adhesive, giving excellent carry down.
- Suitable for a wide range of trackside lubricators and grease delivery systems.
- Will not migrate to top of rail.
- Continuous performance across multi-seasons
- Inherently biodegradable

Typical Characteristics

Appearance	Visual	Smooth
Colour	Visual	Black/Grey
Thickener Type		Complex
Temperature Range		-30°C - 120°C (-22°F - 248°F)
Worked Penetration	IP 50	290 - 320
Drop Point	IP 396	160°C / 320°F
Oil Separation (40°C, 168hrs)	IP 121	<5%
4-Ball Wear Scar	IP 239	0.6mm
4-Ball Weld Load	IP 239	620kg
Emcor Corrosion (distilled water)	IP 220	0,0
Copper Corrosion (100°C, 24hrs)	IP 122	1a
Biodegradability	OECD 301B	Inherently

Base Oil Characteristics

Type		Mineral
Kinematic Viscosity (40°C)	ASTM D445	100cSt
Flash Point	IP 34	>220°C / 428°F



The information contained herein may change. Whilst every care is taken to ensure the accuracy of the material contained in this bulletin, no liability can be assumed for the information given. For specific, current information please contact Clare field sales staff.