

RAIL

High performance, curved rail lubricant

Innovating for tomorrow



TECHNICAL DATA SHEET

Product code: D0093
Quality Standards:
ISO 9001:2015
ISO 14001: 2015
Issue Date—July 2018
Revision—01

ClareTech Rail King

High performance curved rail grease for trackside lubricators.
NLGI 1.5

Applications

Rail King is for use in trackside lubricators wherever there is a need for a high performance and consistent delivery over a wide temperature range. Suitable for high traffic networks and heavy axle loads.

Features and Benefits

- Clean to use
- Economical
- Enhanced anti-wear performance
- Excellent corrosion protection
- Excellent adhesion to gauge corner
- High load protection with high EP properties
- Suitable for a wide range of trackside lubricators and grease delivery systems
- Will not migrate to top of rail
- Inherently Biodegradable

Typical Characteristics

Appearance	Visual	Smooth
Colour	Visual	Beige
Thickener Type		Complex
Temperature Range		-30°C to 120°C (-22°F - 248°F)
Worked Penetration	IP 50	290—320
Drop Point	IP 396	170°C
Oil Separation (40°C, 168hrs)	IP 121	<5%
4-Ball Wear Scar	IP 239	0.6mm
4-Ball Weld Load	IP 239	620kg
Emcor Corrosion (distilled water)	IP 220	0,0
Copper Corrosion (100°C, 24hrs)	IP 122	1a
Water Wash Out	ASTM D1264	5%
Biodegradability	OECD 301B	Inherently Biodegradable

Base Oil Characteristics

Type		Mineral
Kinematic Viscosity (40°C)	ASTM D445	100cSt
Flash Point	IP 34	>220°C



The information contained herein may change. Whilst every care is taken to ensure the accuracy of the material contained in this bulletin, no liability can be assumed for the information given. For specific, current information please contact Clare field sales staff.