

Advanced Railway Friction Management Solutions **Innovating for tomorrow** 



Quality Standards: ISO 9001:2015 ISO 14001: 2015 Issue Date— Jun 2024 Revision—04

## ClareShield EcoStick WFS

**Environmentally Friendly Wheel Flange Stick Lubricant** 

## **Description**

ClareShield EcoStick WFS reduces the coefficient of friction, minimises wear of wheel flanges and rail, and reduces noise.

ClareShield EcoStick WFS is made from annual renewable biocomposite materials, and is biodegradable in the natural environment making it the most environmentally friendly stick lubrication solution on the market.

It is applied to the wheel flange by a constant force, where the material transfers to the wheel/flange and creates a lubricating film at the contact point.

The EcoStick is self-regulating, applying lubrication dependent on friction and lubrication requirements.

## **Features and Benefits**

- Extremely low wear rates meaning each stick lasts and lubricates for longer.
- All materials used are recyclable and/or biodegradable in the natural environment.
- Low mobility and is not expected to bio accumulate.
- The lubrication film created does not hold or attract contaminants.
- Temperature will have a small effect on wear rate
- Economical and reliable method of flange lubrication

Typical Characteristics		
Appearance	Visual	Solid stick, moulded product
Colour	Visual	Black, opaque
Odour		Odourless
Density		.635 +010 oz/in^3
Softening Point		90°C
Hardness	ASTM D2240 -05	Surface hardness 30d +- 3
Toxicity		Product is non-toxic
Flashpoint		>200°C

Available Stick Sizes	
24 x 49 x 57mm	
26 x 26 x 113mm	
24 x 49 x 217mm	
20 x 44 x 51mm	
20 x 44 x 101mm	

<sup>\*</sup> Note: The product will exhibit a slight change of colour after exposure to air. This is a normal and expected feature of the unique chemistry employed in this grease. This feature has been assessed as having no effect on the product performance.



