



## ClareGuard GRL

NLGI 0.5

A thixotropic, bitumen-free wire rope lubricant with advanced corrosion inhibitor.

Applications	
A specially formulated wire rope lubricant, designed for complete lubrication and corrosion protection in wet and hostile applications.	
Features and Benefits	
<ul style="list-style-type: none"> <li>Highly water repellent</li> <li>Highly adhesive to prevent from being wiped from the surface of the rope</li> <li>Non-drip characteristics</li> <li>Contains a sophisticated corrosion inhibitor system</li> <li>Displays a degree of syneresis, which permits a controlled migration of the corrosion inhibitors to uncoated areas of the rope</li> </ul>	
Product Codes	
D0469/00/12.5K	12.5kg
D0469/00/0050K	50kg
D0469/00/N180K	180kg

Typical Characteristics		
Test	Method	Result
Appearance	Visual	Smooth
Colour	Visual	Black
Thickener Type		Inorganic
Operating Temperature Range		Up to 80°C
Unworked Penetration	IP 50	330-360
Drop Point	IP 396	Infusible
4-Ball Weld Load	IP 239	400kgf
4-Ball Wear Scar	IP239	0.55mm
Emcor (Water)	ASTM D6138	0,0
Suggested Application		
Suitable for application via cloth, brush and high-pressure applicator.		